

CSI MasterFormat® 2010 Number: 04 21 13

Mainstreet Collection

Plant

Salisbury, NC

Available Sizes

Modular, Closure, Utility

ASTM Specification

C216, Grade SW, Type FBS


Dimensions	7 5/8" x 2 1/4" x 3 1/2" (Modular), 7 5/8" x 3 5/8" x 3 1/2" (Closure), 11 5/8" x 3 5/8" x 3 1/2" (Utility)
Unit Weight	3.30 lbs. (Modular), 5.50 lbs. (Closure), 8.30 lbs. (Utility)
Core Configuration	3-Hole (Modular, Closure), 5-Hole (Utility) <25% void area
Compressive Strength, Average	>3,000 psi required >12,000 actual
24-Hour Water Absorption, Average	<8.0% required <7.0% actual
Initial Rate of Absorption	<30 g/min/30in² desired 15-25 g/min/30in² actual
Efflorescence	No
Face Shell Thickness	>3/4"



The Mainstreet Collection is part of Boral's Architectural Design Series and consists of classic red, burgundy and brown commercially-oriented brick products that feature formal edges and a wirecut or smooth texture. Boral's Salisbury, NC facility manufactures Modular, Closure and Utility brick sizes for the Mainstreet Collection. It also offers special shapes for additional design possibilities on your project*.




FULL RANGE WIRECUT
Item code 082.0096




RED RANGE SEMI SMOOTH
Item code 082.0198




RED RANGE WIRECUT
Item code 082.0199



BURGUNDY WIRECUT
Item code 082.0712



CHOCOLATE WIRECUT
Item code 082.0070



WIRECUT SAVOY
Item code 082.0316

Note: The brick colors displayed in this document attempt to represent the general look of a product; however, variations in printers, monitors and photography may create visual differences when compared to actual brick. Always confirm your selection from actual samples, available from your Boral sales professional. Run-to-run testing data may vary within ASTM tolerances.

* Special shapes are made to order, drawings must be submitted for review and approval.